



C RIGHT EXTERIOR ELEVATION

D LEFT EXTERIOR ELEVATION

GENERAL NOTES

- CONTRACTOR SHALL VERIFY ALL EXTERIOR MATERIALS, COLORS AND FINISHES WITH THE ARCHITECT. ANY DISCREPANCIES NOTED SHALL BE BROUGHT TO THE ATTENTION OF THE ARCHITECT FOR CLARIFICATION.
- PROVIDE EXPANSION JOINTS (E.J.) AS LOCATED ON ELEVATIONS. CAULKING SPECIFICATION FOR EXPANSION JOINTS SHALL BE "ADOBETAN" (SL-2) BY TREMCO.
- MAXIMUM SPACING OF EXPANSION JOINTS ARE TO BE 20'-0" O.C.
- ALL ROOF TOP EQUIPMENT UNITS SHALL BE FULLY SCREENED BY THE BUILDING PARAPET WALL ON EACH SIDE OF THE BUILDING.

EXTERIOR MATERIAL LEGEND

EXTERIOR PAINT	
EP-1	EXTERIOR METALS - PAINT TO MATCH ENGLERT METAL ROOF COLOR DK. BRONZE
STUCCO	
ST-1	3-COAT STUCCO SYSTEM (FINE FINISH) - 3/4" MINIMUM THICKNESS UNLESS NOTED OTHERWISE. COLOR TO MATCH SHERWIN WILLIAMS #6113 - INTERACTIVE CREAM
ST-2	3-COAT STUCCO SYSTEM (FINE FINISH) - 3/4" MINIMUM THICKNESS UNLESS NOTED OTHERWISE. COLOR TO MATCH SHERWIN WILLIAMS #6094 - SENSATIONAL SAND
STACKED STONE	
SS-1	ASPEN COUNTRY LEDGESTONE BY BORAL (DRY STACK APPLICATION)
STONE BAND ( LOWER BAND ONLY )	
SB-1	TUSCAN UNTEL CHAMPAGNE BY BORAL
AWNING	
AW-1	ALUMINUM AWNING SYSTEM - SELECTED BY OWNER
AW-2	ALUMINUM AWNING SYSTEM - SELECTED BY OWNER STANDING SEAM METAL AWNING, COLOR: DARK BRONZE
STUCCO - SYNTHETIC STUCCO (EIFS)	
EF-1	"FINE FINISH" APPLICATION; COLOR TO MATCH SW #6113 "INTERACTIVE CREAM"
EF-2	"FINE FINISH" APPLICATION; COLOR TO MATCH SW # 6094 "SENSATIONAL SAND"
WINDOW SILLS	
SW-1	MOCHA WATERTABLE/SILL BY BORAL
METAL	
M-1	PREFINISHED 4" 2-PIECE COMPRESSION METAL COVER. METAL TO MATCH ENGLERT METAL ROOF COLOR DARK BRONZE
M-2	1" PREFINISHED ALUMINUM COMPOSITE PANEL SYSTEM, REYNOLDBOND - COLOR TO MATCH ALUMINUM STOREFRONT SYSTEM
M-3	METAL TO MATCH ENGLERT METAL ROOF COLOR DARK BRONZE
M-4	VISTAWALL FG-3000 STOREFRONT SYSTEM PREFINISHED DARK BRONZE ANODIZED ALUMINUM AA-MI2C22444
M-5	PREFINISHED ALUMINUM DRIP EDGE
M-6	ENGLERT METAL ROOF SYSTEM SERIES 2000; 1-3/4" HIGH STRUCTURAL SNAP LOCK STANDING SEAM WITH NO BATTEN. PANELS ARE 18" WIDE, 24 GAUGE GALVALUME WITH BAKED-ON PERMACOLOR 2000 KYNAR 500 IN SMOOTH FINISH WITH (2) 1/8" HIGH x 1/8" WIDE STRAIN RIBS TO BE SPACED TO DIVIDE INTO THREE EQUAL PARTS; COLOR TO MATCH DARK BRONZE
GLASS - SEE A600 FOR WINDOW FRAME DIMENSIONS	
GL-1	1-5/16" IMPACT RATED INSULATED LAMINATED GLASS - CLIMATE ZONES 1 OR 2. IGU AT STOREFRONT 0.60 U-FACTOR, SHGC PFS0.5 = 0.40. PPG SOLARBAN 70 XL LOW-E #2 (STOREFRONT WINDOWS & DOORS)
GL-2	1-5/16" IMPACT RATED FROSTED INSULATED LAMINATED GLASS - CLIMATE ZONES 1 OR 2. IGU AT STOREFRONT 0.60 U-FACTOR, SHGC PFS0.5 = 0.40. PPG SOLARBAN 70 XL LOW-E #2 SATIN ETCH #4 (RESTROOM TRANSOM PANEL)
GL-3	1" NON-IMPACT RATED INSULATED BLACK SPANREL GLASS WINDOW
LIGHTING	
EL-1	SECURITY LIGHT - SEE ELECTRICAL DRAWINGS
EL-2	DECORATIVE POLE LIGHT - SEE ELECTRICAL DRAWINGS



B REAR EXTERIOR ELEVATION



A FRONT EXTERIOR ELEVATION